

Applicants: B. Ferek-Petric  
Serial No. 10/085,072  
Page 2

### **IN THE SPECIFICATION**

Please replace the paragraph on page 5 at lines 23-35 with the following substitute paragraph:

IMD 10 in Figure 3 is most preferably programmable by means of an external programming unit (not shown in the figures). One such programmer is the commercially available Medtronic Model 9790 programmer, which is microprocessor-based and provides a series of encoded signals to MD 10, typically through a programming head that transmits or telemeters radio-frequency (RF) encoded signals to IMD 10. Such a telemetry system is described in U.S. Patent No. 5,312,453 to ~~Wyborny et al.~~, hereby incorporated by reference herein in its entirety. The programming methodology disclosed in the Wyborny et al.'s '463 patent is identified herein for illustrative purposes only. Any of a number of suitable programming and telemetry methodologies known in the art may be employed so long as the desired information is transmitted to and from the pacemaker.

Please replace the paragraph on page 6 at lines 19-32 with the following substitute paragraph:

Electrical components shown in Figure 3 are powered by an appropriate implantable battery power source 76 in accordance with common practice in the art. For the sake of clarity, the coupling of battery power to the various components of IMD 10 is shown in the Figures. Antenna 56 is connected to input/output circuit 54 to permit uplink/downlink telemetry through RF transmitter and receiver telemetry unit 78. By way of example, telemetry unit 78 may correspond to that disclosed in U.S. Patent No. 4,~~566,063~~ 4,556,063 issued to Thompson et al., hereby incorporated by reference herein in its entirety, or to that disclosed in the above-referenced '453 patent to ~~Wyborny et al.~~ It is generally

Applicants: B. Ferek-Petric  
Serial No. 10/085,072  
Page 3

preferred tha the particular programming and telemetry scheme selected permit the entry and storage of cardiac rate-responsive parameters. The specific embodiments of antenna 56, input/output circuit 54 and telemetry unit 78 presented herein are shown for illustrative purposes only, and are not intended to limit the scope of the present invention.